

CLAIMS

1. A sealing bag with a chuck, comprising:

a bag body which opens on one side; and

5 a chuck having a pair of tapes bonded near an opening part of the bag body and opposed to each other along the opening part of the bag body, and a pair of female and male clamping parts formed on the faces of the pair of tapes opposed to each other and disengageably
10 clamping with each other along the opening part of the bag body to openably/closably seal the bag body, the sealing bag further comprising:

projected parts formed in projected lines at the bag body opening side edge parts of the pair of tapes and
15 integrally projected to inner and outer face sides of the bag body,

the pair of tapes being bonded to the inside of the opening part in the inner face of the bag body in such a manner that the projected parts are positioned inside the
20 opening edge part of the bag body.

2. The sealing bag with the chuck according to claim 1, wherein the projections disposed on the pair of tapes are not thermally fused onto the inner face of the
25 bag body, when the pair of tapes are bonded to the inner face of the bag body by thermal fusion.

3. The sealing bag with the chuck according to claim 1 or 2, wherein the projected parts are disposed in
30 the same position with respect to a depth direction of the

bag body.

4. The sealing bag with the chuck according to claim 3, wherein a maximum width of the projected part in a projecting direction inside and outside the bag body is 0.3 mm or more and is not more than a distance between the faces of the tapes opposed to each other.

5. The sealing bag with the chuck according to claim 3, wherein a maximum width of the projected part in a projecting direction on inner and outer face sides of the bag body is 0.5 mm or more and is 1/2 or less of a distance between the faces of the tapes opposed to each other.

6. The sealing bag with the chuck according to claim 1 or 2, wherein the projected parts are disposed in different positions with respect to a depth direction of the bag body.

7. The sealing bag with the chuck according to claim 6, wherein a maximum width of the projected part in a projecting direction on inner and outer face sides of the bag body is 0.3 mm or more and 2.0 mm or less.

8. The sealing bag with the chuck according to claim 6, wherein a maximum width of the projected part in a projecting direction on inner and outer face sides of the bag body is 0.5 mm or more and 2.0 mm or less.

9. The sealing bag with the chuck according to

claim 6, wherein a maximum width of the projected part in a projecting direction on inner and outer face sides of the bag body is 0.3 mm or more and is not more than a distance between the faces of the tapes opposed to each other.

5

10. The sealing bag with the chuck according to claim 6, wherein a maximum width of the projected part in a projecting direction on inner and outer face sides of the bag body is 0.5 mm or more and is not more than a distance between the faces of the tapes opposed to each other.

10

11. The sealing bag with the chuck according to claim 6, wherein a shift of the projected part in a depth direction of the bag body is in a range of 1.0 mm to 2.0 mm.

15

12. The sealing bag with the chuck according to any one of claims 1, 2, 4, 5, and 7 to 11, wherein the projected part constitutes a protruded line having a circular sectional shape.

20

13. The sealing bag with the chuck according to any one of claims 1, 2, 4, 5, and 7 to 11, wherein the projected part constitutes a protruded line having an angled sectional shape.

25